

SIZE RANGE

PRESSURE RATING

ACCESSORIES / OPTIONS

SUGGESTED SPECIFICATIONS

M&H VALVE—MUD VALVES (4”-24”) STYLE 140-02

SIZE RANGE	WORKING PRESSURE
4”-24”	Mud valves are recommended for use in lines of low seating or unseating pressures only.

<u>Available End Connections</u>	<u>Size Range</u>	<u>Style No.</u>
Flanged End, (Non-Rising Stem)	4”-24”	140-02
Flanged End, (Rising Stem)	4”-12”, 16”, 18”	1040-02

Accessories / Options:

Hand wheels

“T” Handles

2” Square Operating Nuts

Stem Guides

Floor stands (Non-rising (NRS) / Rising Stem (RS))

Floor boxes

Extension Stems---(Consult Factory Rep or Distributor for material other than cold rolled steel.)

NOTE: Consult Factory for special applications or sliding stems.

SUGGESTED SPECIFICATIONS:

The Mud valve shall be of the heavy duty flanged type designed to provide a positive seal under both seating and unseating head conditions. The Valve shall be (non-rising) stem style as detailed on the schedule or the plans.

The frame, yoke and gate shall be sturdily proportioned for strength and rigidity and be of cast iron conforming to ASTM specifications A126 Class B.

The stem, and stem nut shall be bronze. The stem shall be machined with accurately cut modified acme threads.

The seat ring shall be bronze with a tapered, accurately machined seating face. The plug seat shall be a seamless molded ring of BUNA-N tapered to accurately mate with the seat ring to form a positive seal.

Mud valves shall be F-3075-T non-rising stem design or F-3085-T rising stem design as furnished by M&H Valve or approved equal.

July 2005 / M&H Mud Valves