

# SPECIFICATIONS / AVAILABLE CONFIGURATIONS / STYLE NUMBERS M&H LIST 16 EXTRA HEAVY PRESSUE DOUBLE DISK GATE VALVES

## M&H List 16 Double Disc Parallel Seat IBBM Gate Valves Meet or Exceed the requirements of AWWA C500

Size Range	Water Working Pressure psi	Hydrostatic Shell Test psi
4" – 12"	250	500
24" – 30"	225	450

<b>Available End Connections</b>	<b>Size Range</b>	<b>Figure No.</b>
Flanged Ends (NRS)	4"-48"	F-5300
Flanged Ends (OS&Y)	14"-48"	F-5305

**Notes:**

Flanges are faced and drilled to ANSI Class 250 Standard

Call Factory for Special Applications

Contact Factory for availability, lead time, dimensional drawings on 36" through 48"

Contact Factory for Flanges drilled to ANSI Class 125lb standard

**Accessories:**

Floor stands

Limit Switches

Open Gearing

Needle & Slot (Navy) Indicators

Electric Motors

2" Square Operating Nuts

Chain wheels

"T" Handles

Stem Guides

Indicator Posts

By-pass Valves

Enclosed Gearing (Grease Case)

Barrel Indicators

Tracks, Rollers, & Scrapers for valves 14" or larger installed horizontally in line

Hand wheels

Extension Stems

Floor boxes