SPECIFICATIONS STYLE NUMBERS (4"x 6" to 10" x 12") M&H AWWA C508 INCREASING FLANGED CHECK VALVES

vr	e / Facing Material / Opti	ons Range	Style Number	Drawing Number
	4" x 6 to 10" x 12"	200	400	400
		Pressure psi		Test psi
	Size Range	Water Working	Seat Test Psi	Hydrostatic Shell

INCREASING CHECK						
4" x 6" to 10"x12"	3059-02A	ICV-A1-PC				
4" x 6" to 10"x12"	3059-02	ICV-A1-PC				
4" x 6" to 10"x12"	3159-02A	ICV-A1-LW				
4" x 6" to 10"x12"	3159-02	ICV-A1-LW				
4" x 6" to 10"x12"	3259-02A	ICV-A1-LS				
4" x 6" to 10"x12"	3259-02	ICV-A1-LS				
	4" x 6" to 10"x12" 4" x 6" to 10"x12" 4" x 6" to 10"x12" 4" x 6" to 10"x12" 4" x 6" to 10"x12"	4" x 6" to 10"x12"3059-024" x 6" to 10"x12"3159-02A4" x 6" to 10"x12"3159-024" x 6" to 10"x12"3259-02A				

NOTE: In addition to Dual Arms, Limit Switches & Tapped Cover, M&H also can provide check valves with special coatings and tapped bosses. See drawing CV-TB in the "Standard Flanged Check Valve Section" for location and sizes of tapped bosses.

September 1, 2012 / C508 Check Valves